

MV-2 МИКРО ВИБРОМОТОРИ

Микровибрационният двигател MV-2 е реализиран за приложения, които изискват изключително компактни габаритни размери.
ВХОДНО ЕЛЕФАЗНО НАПРЕЖЕНИЕ,

СКОРОСТ НА ВИБРАЦИЯ: 2 полюса 3000 d / d 50 Hz - 3600 d / d 60Hz
ПО ЗАЯВКА:

Прахово боядисване Blue Ral 5010 за тялото - крайни капаци INOX.

Трифазният вибрационен двигател MV-2 е оборудван с 1 метър електрически кабел.



MV-2 Micro Vibrations Motor

The micro vibration motor MV-2 has been realized for applications which require extremely compact overall dimensions.

INPUT VOLTAGE SINGLE-PHASE,

With standard executions at : 220-230V 50Hz ve 110-115V 60 Hz.

THREEPHASE, SINGLE VOLTAGE, With standard executions at 220-230V 50Hz or 380-400V 50Hz ve 230V and 460V 60Hz.

VIBRATION SPEED : 2 Poles 3000 d/d 50 Hz – 3600 d/d 60Hz

ON REQUEST :

Powder painting Blue Ral 5010 for the body - INOX end covers.

The single-phase vibration motor MV-2 is equipped with a starting capacitor and 2 mt. electrical cable.

The threephases vibration motor MV-2 is equipped with 1mt. electrical cable.

Model Type	Честота Frequency (Hz)	Обороти rpm	Центробежна сила Centrifugal Force (Kg/F)	Тегки Weight (Kg)	Мощност Input Power (W)	Номинален ток Nom. Current (A)
MONOFAZE - MONOPHASE - MONOPHASE - MONOFASICO						
MV - 2M	50	3000	22	1,6	25	0,15 (230V)
MV - 2M	60	3600	32	1,6	30	0,25 (110V)
TRIFAZE - THREEPHASE - TRIPHASE - TRIFASICO						
MV - 2T	50	3000	22	1,6	24	0,15 (400V)
MV - 2T	60	3600	32	1,6	42	0,29 (230V)

Model Type	Размери - Overall Dimensions (mm)												
	A	B	C	ØD	E	M	L	H	G	I	F	N	O
MV - 2M	144,5	112	65	61	32	32	91	14	7	31	8	54	22
MV - 2T	144,5	112	65	61	32	32	91	14	7	31	8	54	22

